



product description: intended for installation to the distribution of low voltage
 designed for inserting power and communication circuits, security lines and other lines
 possibility to insert partition wall or shielding canal
 possibility to insert an instrument box and subsequently mount common types of instruments
 from a fire point of view halogen-free trunkings are used in areas with an emphasis on the safety of people and property, for example: public buildings, hospitals, schools, theaters, airports, shopping centers ...

material: PC ABS - Pb-free

self-snuffing: yes, within 30 s

temperature resistance: -25 - +90 °C

flaming loop test: 850 °C

impact strength: 1 J

protection types: IP40

fire class for underlying material: A1-F

inside area: 5500 mm²

distance base perforation: 200 ±20 mm

length tolerance: ±10 mm

weight: 890 g/m

meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07

storage: ČSN 64 0090



trunkings are not a breeding ground for bacteria, tested in SZÚ according to ČSN EN ISO 846:2019

List of bacteria that have been tested:

ESCHERICHIA COLI, STAPHYLOCOCCUS AUREUS, KLEBSIELLA PNEUMONIAE, PSEUDOMONAS AERUGINOSA, ENTEROCOCCUS FAECALIS, BACILLUS SUBTILIS, SALMONELLA ENTERICA, LEGIONELLA PNEUMOPHILA, CANDIDA ALBICANS

| item number | length | color | package | package - description | note |
|-------------------|--------|----------------|-------------|-----------------------|--------------|
| PK 110X65 D HF_HD | 2 m | white RAL 9003 | 6 m | carton | - |
| 8211HF_HB | | white RAL 9003 | 2 / 310 pcs | foil / carton | end |
| 8212HF_HB | | white RAL 9003 | 2 / 110 pcs | foil / carton | connecting |
| 8213HF_HB | | white RAL 9003 | 2 / 54 pcs | foil / carton | bending |
| 8214HF_HB | | white RAL 9003 | 2 / 58 pcs | foil / carton | branching |
| 8215HF_HB | | white RAL 9003 | 2 / 30 pcs | foil / carton | inner corner |
| 8216HF_HB | | white RAL 9003 | 2 / 60 pcs | foil / carton | outer corner |
| 8217HF_HB | | white RAL 9003 | 2 / 200 pcs | foil / carton | grommet |

recycling symbols:



PA - ABS trunking, PC - ABS covers



Protective film, adhesive tape, packaging film for trunkings, bags, and packaging film for covers



cardboard

usage of inner trunking cross-section (60%):

| orientation cable diameter (mm) | 6 | 7 | 8 | 8,5 | 9 | 9,5 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
|---------------------------------|----|----|----|-----|----|-----|----|----|----|----|----|----|----|
| number of inserted cables | 60 | 45 | 36 | 30 | 30 | 25 | 22 | 19 | 15 | 13 | 12 | 9 | 8 |

Risks Associated with Product Use:

during installation, use appropriate protective work equipment and follow safety guidelines

use the product only for the purposes intended by the manufacturer

use the product in an environment that complies with the manufacturer's instructions

do not use the product if it is damaged

follow the manufacturer's recommendations and do not exceed the number of inserted cables or the product's load capacity

after installation, check the correctness of the mounting of trunkings and covers according to the manufacturer's recommendations

accessories:

instrument box KP 80 PK HF_HB, KP PK HF_HB

partition walls PEKE 60 HF_HD