


**product description:**

designed for distribution system with voltage 400 V and with maximum current 16 A  
intended for devices of Tango - ABB series  
suitable for devices with great mounting depth  
on the sides of the box are marked inlets for the trunkings  
to install on materials with fire classes E or F, use insulating pad  
can achieve IP 40 while used with cover VLK 80/T

material: PVC (HB, SD, I2) / PC-ABS (I1, FB)

color: white / imitation pink birch / imitation dark oak / light brown / black

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-D

weight: 44 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

LK 80X28 T\_HB - 10 pcs of boxes including device screws packed in foil; 100 pcs of boxes in carton; color - white

LK 80X28 T\_I1 - 10 pcs of boxes including device screws packed in foil; 100 pcs of boxes in carton; color - imitation pink birch

LK 80X28 T\_I2 - 10 pcs of boxes including device screws packed in foil; 100 pcs of boxes in carton; color - imitation dark oak

LK 80X28 T\_SD - 10 pcs of boxes including device screws packed in foil; 100 pcs of boxes in carton; color - light brown

LK 80X28 T\_FB - 10 pcs of boxes including device screws packed in foil; 100 pcs of boxes in carton; color - black

**accessories:**

screwless terminal plates TYP015, TYP016, TYP017, TYP018

cover VLK 80/T

extending frame NRT (white)

thermo-insulating pad PI 80 T

terminal plate S-66

