




product
description:

designed for distribution system with voltage 400 V and with maximum current 16 A

for installation in environment with increased humidity, dust, chemical and corrosion resistance, in environments with increased risk of mechanical damage

universal sealing grommets for cables and pipes (Ø16, 25, 32, 40 mm)

to install on materials with fire classes E or F, use thermally insulating pad

material: PVC

color: light gray RAL 7035 / dark gray RAL 7012

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 650 °C

fire class for underlying material: A1-D

protection types: IP 54

weight: 640 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

8118_LA - sealing grommets, terminal plate and cover screws placed in the box, each box packed in shrink foil and labelled; 24 pcs of boxes stacked in a carton; color - dark gray RAL 7012

8118_KA - sealing grommets, terminal plate and cover screws placed in the box, each box packed in shrink foil and labelled; 24 pcs of boxes stacked in a carton; color - light gray RAL 7035

accessories:

terminal plate S-96; SP-96

screwless terminal plates TYP015, TYP016, TYP017, TYP018

sealing grommet 1618

recycling symbols



box



foil



cardboard



screws

 WARNING

risks associated
with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person

follow the manufacturer's installation instructions according to the installation instructions and videos

damage to the product - if the box is visibly damaged, stop using it

under normal and foreseeable conditions of use, the installed box does not pose any risks to consumers